





ACTIVE LIGHTING LTD

Optimizing energy conservation and efficiency

No.	Code No.	Picture	Description	Parameters	Application	View Angle	Packing Info
2	MFW8B4D		<ul style="list-style-type: none"> @ Constant current design; @ Constant Power design; @ Customized AC LED; @ Fuse inside; @ Waterproof IP67; @ Fireproof 94V-0; @ Over load protection; @ Short circuit protection; @ Over temperature protection; @ ABS injection; @ Beam angle 160°; @ 6500 -7000K; @ Size:88*21.5*11.1mm @ 100pcs/string 	Voltage: 220-240VAC Power: 1.6W Lumen/pc : 140Lm Center Distance: 200mm Cable:UL1672/AWG22/L=200m Cuttable: 1pcs	6~15cm depth channel letters or light boxes	160*160 °	Carton size: 63*34*29cm 100pcs/box, 5boxes/carton on 500pcs / carton NW: 15KGS GW: 16KGS
1	MFW8A3D		<ul style="list-style-type: none"> @ Constant current design; @ Constant Power design; @ Customized AC LED; @ Fuse inside; @ Waterproof IP67; @ Fireproof 94V-0; @ Over load protection; @ Short circuit protection; @ Over temperature protection; @ ABS injection; @ Beam angle 155 °; @ 6500 -7000K; @ Size:110*28*8.5mm @ 100pcs/string 	Voltage: 220-240VAC Power: 2.5W Lumen/pc : 200Lm Center Distance: 353mm Cable:UL1672/AWG18/L=250m Cuttable: 1pcs	12~30cm depth channel letters or light boxes	155°	Carton size: 53*38*36cm 100pcs/bag , 20bags/carton on 500pcs / carton NW: 21KGS GW: 22KGS
3	MFW8F3D		<ul style="list-style-type: none"> @ Constant current design; @ Constant Power design; @ Customized AC LED; @ Fuse inside; @ Waterproof IP68; @ Fireproof 94V-0; @ Over load protection; @ Short circuit protection; @ Over temperature protection; @ ABS injection; @ Beam angle 160 °; @ 6500 -7000K; @ Size:57*16*10.5mm @ 100pcs/string 	Voltage: 220-240VAC Power: 1.0W Lumen/pc : 99Lm Center Distance: 200mm Cable: UL1007/AWG20/ L=140mm Cuttable : 1pc	6~12cm depth channel letters or light boxes	160°	Carton size: 45*25*26cm 100pcs/bag , 5bags/carton on 500pcs / carton NW: 7.3KGS GW: 7.9KGS
4	MFW8C3D		<ul style="list-style-type: none"> @ Constant current design; @ Constant Power design; @ Customized AC LED; @ Fuse inside; @ Waterproof IP65; @ Fireproof 94V-0; @ Over load protection; @ Short circuit protection; @ Over temperature protection; @ ABS injection; @ Beam angle 160 °; @ 6000 -6500K; @ Size:150*86*9.5mm @ 50pcs/string 	Voltage: 220-240VAC Power: 6.0W Lumen/pc : 495Lm Center Distance: 545mm Cable:UL1672/AWG18/L=400m Cuttable: 1pcs	10~30cm depth light boxes	160°	Carton size: 56*26*20.4cm 50pcs/box, 2boxes/carton on 200pcs / carton NW: 14KGS GW: 15.5KGS

Email: sunil@activelighting.co.nz

Phone: +649 625 1265

Mobile: +6421 875238

www.activelighting.co.nz

61 Seacliffe Road Hillsborough Auckland 1042 New Zealand